

Inkjet Specifications

Interface & Communication

- ◆ 7" TFT color screen, with int'l standard QWERT keypad
- ◆ USB port, to save/restore text & config, to load logos from pc to printers, to upgrade software
- ◆ Ethernet port (10/100MB)
- ◆ RS232/485 port

Electronic & Software Features

- ◆ 32 digits embedded LINUX operation system
- ◆ User friendly interface, WYSIWYG display
- ◆ Storage memory 40MB
- ◆ "RUN/STOP" hot key to start/shut down printer automatically
- ◆ "INFO" hot key to list the history of errors to ease maintenance
- ◆ "PRINT MENU" hot key to activate printing instantly
- ◆ USB/Ethernet software upgrading
- ◆ Pop-up window to remind changing filters in every 2,000 hours
- ◆ Real time and date with calendar
- ◆ Four print mode: High Speed, Standard, Graphic, Multi line high speed
- ◆ Text format: Horizontal reverse, Vertical-reverse, Negative, Double Space, Bold, Character Width
- ◆ Defined grid value to move the editing cursors at a certain dot you need
- ◆ 3 counters & 4 shifts, automatically
- ◆ Build-in graphic/logo editing software as standard, full screen
- ◆ OPS(Encoder Direction Recognition & Printing Compensation Function)
- ◆ DMS(Distance Measuring System)
- ◆ Passwords give accesses to different level of users
- ◆ Multi operation language available
- ◆ Instruction/training movie clips play function via USB disk, optional

Printing Features

- ◆ EXP, MFG, Batch No., Logo, Auto/real time/date, Julian date, Shift, Counters, Numbering
- ◆ 24 dots vertically, upto 3 lines printing
- ◆ Multi-fonts available, can be customized upon request
- ◆ Printing speed(single line) 300m/min (5x5)
- ◆ Direct input Arabic/Chinese/Farsi/Russian character with keypad

Hydraulic System

- ◆ Compact design
- ◆ Diaphragm pumps with reliability, longer life, low maintenance cost than gear pump, no direct friction with pigment ink to ensure longer life & high contrast printing, with overload protection
- ◆ Detector in solvent bottle to give alarm when no sufficient solvent

Ink Range

- ◆ Full range of inks available

Certification/Standard approved

- ◆ TUV/ISO9001
- ◆ CE (EMC, MD&LVD)

Physical Features

- ◆ Printer house/Cabinet IP54 stainless steel
- ◆ Umbilical hose standard Length 2,500mm, Diameter 20mm
- ◆ Printer dimension H550xW330xD320mm
- ◆ Print head dimension H180xW43xD44mm
- ◆ G W 30KG
- ◆ Power supply Single phase, 110~220V, 50/60HZ
- ◆ Electrical plug, multi type available
- ◆ Work temperature 5~45C(35~100F)
- ◆ Work humidity max 90% R H, non-condensing


Optional Accessories

- ◆ Photo sensor
- ◆ Shaft encoder
- ◆ Alarm system, 3 colors
- ◆ Conveyor
- ◆ Condensor, Solvent recovery system
- ◆ Sliding table
- ◆ PC logo software

Metronic-Handyware Shanghai Ltd

T15-1-4, No 999 Ningqiao Rd., Jinqiao EPZ
Pudong New District, Shanghai 201206
T +86-21 5834-8225
F +86-21 5934 8193
Email info@rottweilglobal.com
Website www.rottweilglobal.com

Rottweil
Easy to ceiling



E JET
Continuous inkjet printer



Easy



Endurable



Economical

simple
easy
reliable
endurable